

PAN Fiber Packing

Code: KXTP603



Description

Braided from high strength PAN fiber pre-impregnated with PTFE and special lubrication. Re-impregnated during square moulding. It has excellent properties, lubricating and resistance to chemicals.

KXT-P603R -- PAN Fiber Packing with Rubber Core

Rubber core can absorb vibration, to control leakage, suitable for worn-out pumps.



Item no.: KXTP603

PAN Fiber Packing

Item no.: KXTP603

* Especially for condition of middle temperature, pressure, speed

* Contamination is not permitted conditions.

Typical Application

* Wide variety of uses throughout a plant

* Pumps and valves, and can handle more chemicals except strong acid, strong alkali and strong oxidizer

Technical Data

| Material | 100% PAN fiber and PTFE |
|-------------------|------------------------------|
| Temperature Range | -50 up to +260 oC atmosphere |
| Rotating | 20 bar |
| Reciprocating | 80 bar |
| Static | 100 bar |
| Shaft Speed | 20 m/s in rotary |
| PH | 1~13 |
| Density | 1.3g/cm3 |

Copyright © 2014-2015

Ningbo Kaxite Sealing Materials Co., Ltd.

No.134,Huancheng North Road,Jiangbei District,Ningbo City,Zhejiang Province,China (Zip:315020)

Website:<http://www.seal-china.com> E-mail:sales@seal-china.com,kaxite@seal-china.com